




15KVA 220 VOLTS TO 460 VOLTS THREE PHASE AUTOTRANSFORMER



\$2,428.00 CAD

Three Phase Autotransformer with a capacity of 15kVA, transforming 220Y Volts to 460Y Volts

SKU: RC15C2-H1

Categories: [Autotransformer](#)

SCHEMATIC/DIAGRAM AND DIMENSION PICTURES



Three Phase Autotransformer with a capacity of 15kVA, transforming 220Y Volts to 460Y Volts



PRODUCT SPECIFICATIONS

Weight	58 lbs
Phases	3
kVA	15
Connection	3PhA-NT-1
Primary Voltage	220
Primary Max Current	39.4A
Primary Markings	X1-X2-X3
Primary Terminals	#2-14 AWG
Secondary Voltage	460
Secondary Max Current	18.8A
Secondary Markings	H1-H2-H3
Secondary Terminals	Terminal Blocks
Primary Taps	N/A
Conductor Material	Copper
Insulation Class	220°C (Class H)
BIL (Insulation) Level	10kV
Efficiency (@35% Load) %	N/A
Impedance Range	1.5 – 3.5%
Sound (db)	40
Enclosure Type	NEMA 1
Enclosure Size	E1-3
Finish/Colour	Polyester Powder Coat – ANSI/ASA 61 Grey
Standards & Certifications	CSA Certified File No. LR34493, UL Listed File No. E108255, ISO 9001:2015 Registered



OFFICIAL QUOTE

15KVA 220 VOLTS TO 460 VOLTS

THREE PHASE AUTOTRANSFORMER



Country/Manufacturer	Canada/RPM
----------------------	----------------------------