



**15KVA 230 VOLTS TO 277 VOLTS
THREE PHASE AUTOTRANSFORMER**



**15KVA 230 VOLTS TO 277
VOLTS THREE PHASE
AUTOTRANSFORMER**


\$1,533.10 CAD

Three Phase Autotransformer with a capacity of 15kVA, transforming 230Y Volts to 277Y Volts

SKU: RC15C1-D

Categories: [Autotransformer](#)

SCHEMATIC/DIAGRAM AND DIMENSION PICTURES



Three Phase Autotransformer with a capacity of 15kVA, transforming 230Y Volts to 277Y Volts



PRODUCT SPECIFICATIONS

Weight	20 lbs
Phases	3
kVA	15
Connection	3PhA-NT-1
Primary Voltage	230
Primary Max Current	37.7A
Primary Markings	X1-X2-X3
Primary Terminals	#2-14 AWG
Secondary Voltage	277
Secondary Max Current	31.3A
Secondary Markings	H1-H2-H3
Secondary Terminals	Terminal Blocks
Primary Taps	N/A
Conductor Material	Copper
Insulation Class	180°C (Class F)
BIL (Insulation) Level	10kV
Efficiency (@35% Load) %	N/A
Impedance Range	0.5 – 1.5%
Sound (db)	40
Enclosure Type	NEMA 1
Enclosure Size	E1-1
Finish/Colour	Polyester Powder Coat – ANSI/ASA 61 Grey
Standards & Certifications	CSA Certified File No. LR34493, UL Listed File No. E108255, ISO 9001:2015 Registered



OFFICIAL QUOTE
15KVA 230 VOLTS TO 277 VOLTS
THREE PHASE AUTOTRANSFORMER



Country/Manufacturer	Canada/RPM
----------------------	----------------------------