



15KVA 277 VOLTS TO 347 VOLTS THREE PHASE AUTOTRANSFORMER


\$1,408.00 CAD

Three Phase Autotransformer with a capacity of 15kVA, transforming 277Y Volts to 347Y Volts

SKU: RC15D-E

Categories: [Autotransformer](#)

SCHEMATIC/DIAGRAM AND DIMENSION PICTURES



Three Phase Autotransformer with a capacity of 15kVA, transforming 277Y Volts to 347Y Volts



PRODUCT SPECIFICATIONS

Weight	20 lbs
Phases	3
kVA	15
Connection	3PhA-NT-1
Primary Voltage	120/240
Primary Max Current	31.3A
Primary Markings	X1-X2-X3
Primary Terminals	Terminal Blocks
Secondary Voltage	347
Secondary Max Current	25A
Secondary Markings	H1-H2-H3
Secondary Terminals	Terminal Blocks
Primary Taps	N/A
Conductor Material	Copper
Insulation Class	220°C (Class H)
BIL (Insulation) Level	10kV
Efficiency (@35% Load) %	N/A
Impedance Range	1.0 – 3.0%
Sound (db)	40
Enclosure Type	NEMA 1
Enclosure Size	E1-1
Finish/Colour	Polyester Powder Coat – ANSI/ASA 61 Grey
Standards & Certifications	CSA Certified File No. LR34493, UL Listed File No. E108255, ISO 9001:2015 Registered



OFFICIAL QUOTE

15KVA 277 VOLTS TO 347 VOLTS

THREE PHASE AUTOTRANSFORMER



Country/Manufacturer	Canada/RPM
----------------------	----------------------------