


OFFICIAL QUOTE

15KVA 380 VOLTS TO 208 VOLTS THREE PHASE AUTOTRANSFORMER





15KVA 380 VOLTS TO 208 VOLTS THREE PHASE AUTOTRANSFORMER

\$2,207.80 CAD

Three Phase Autotransformer with a capacity of 15kVA, transforming 380Y Volts to 208Y Volts

SKU: RC15F-B

Categories: <u>Autotransformer</u>

SCHEMATIC/DIAGRAM AND DIMENSION PICTURES





Three Phase Autotransformer with a capacity of 15kVA, transforming 380Y Volts to 208Y Volts



OFFICIAL QUOTE



15KVA 380 VOLTS TO 208 VOLTS THREE PHASE AUTOTRANSFORMER

PRODUCT SPECIFICATIONS

PRODUCT SPECIFICATIONS	
Weight	49 lbs
Phases	<u>3</u>
kVA	<u>15</u>
Connection	<u>3PhA-NT-1</u>
Primary Voltage	380
Primary Max Current	22.8A
Primary Markings	H1-H2-H3
Primary Terminals	Terminal Blocks
Secondary Voltage	208
Secondary Max Current	41.6A
Secondary Markings	<u>X1-X2-X3</u>
Secondary Terminals	#2-14 AWG
Primary Taps	N/A
Conductor Material	Copper
Insulation Class	220°C (Class H)
BIL (Insulation) Level	<u>10kV</u>
Efficiency (@35% Load) %	N/A
Impedance Range	1.5 - 3.5%
Sound (db)	40
Enclosure Type	NEMA 1
Enclosure Size	<u>E1-3</u>
Finish/Colour	Polyester Powder Coat - ANSI/ASA 61 Grey
Standards & Certifications	CSA Certified File No. LR34493, UL Listed File No. E108255, ISO 9001:2015 Registered



OFFICIAL QUOTE

15KVA 380 VOLTS TO 208 VOLTS THREE PHASE AUTOTRANSFORMER



Country/Manufacturer	Canada/RPM
----------------------	------------