



15KVA 440 VOLTS TO 277 VOLTS THREE PHASE AUTOTRANSFORMER

\$1,945.80 CAD

Three Phase Autotransformer with a capacity of 15kVA, transforming 440Y Volts to 277Y Volts

SKU: RC15H2-D

Categories: [Autotransformer](#)

SCHEMATIC/DIAGRAM AND DIMENSION PICTURES



Three Phase Autotransformer with a capacity of 15kVA, transforming 440Y Volts to 277Y Volts



PRODUCT SPECIFICATIONS

Weight	39 lbs
Phases	3
kVA	15
Connection	3PhA-NT-1
Primary Voltage	440
Primary Max Current	19.7A
Primary Markings	H1-H2-H3
Primary Terminals	Terminal Blocks
Secondary Voltage	277
Secondary Max Current	31.3A
Secondary Markings	X1-X2-X3
Secondary Terminals	Terminal Blocks
Primary Taps	N/A
Conductor Material	Copper
Insulation Class	220°C (Class H)
BIL (Insulation) Level	10kV
Efficiency (@35% Load) %	N/A
Impedance Range	1.0 – 3.0%
Sound (db)	40
Enclosure Type	NEMA 1
Enclosure Size	E1-3
Finish/Colour	Polyester Powder Coat – ANSI/ASA 61 Grey
Standards & Certifications	CSA Certified File No. LR34493, UL Listed File No. E108255, ISO 9001:2015 Registered



OFFICIAL QUOTE
15KVA 440 VOLTS TO 277 VOLTS
THREE PHASE AUTOTRANSFORMER



Country/Manufacturer	Canada/RPM
----------------------	----------------------------