

**OFFICIAL QUOTE** 

## 15KVA 440 VOLTS TO 277 VOLTS THREE PHASE AUTOTRANSFORMER





# 15KVA 440 VOLTS TO 277 VOLTS THREE PHASE AUTOTRANSFORMER

# \$1,945.80 CAD

Three Phase Autotransformer with a capacity of 15kVA, transforming 440Y Volts to 277Y Volts

SKU: RC15H2-D Categories: <u>Autotransformer</u>

# SCHEMATIC/DIAGRAM AND DIMENSION PICTURES





Three Phase Autotransformer with a capacity of 15kVA, transforming 440Y Volts to 277Y Volts



**OFFICIAL QUOTE** 

### 15KVA 440 VOLTS TO 277 VOLTS THREE PHASE AUTOTRANSFORMER



#### **PRODUCT SPECIFICATIONS**

Weight	39 lbs
Phases	3
kVA	<u>15</u>
Connection	<u>3PhA-NT-1</u>
Primary Voltage	<u>440</u>
Primary Max Current	<u>19.7A</u>
Primary Markings	<u>H1-H2-H3</u>
Primary Terminals	Terminal Blocks
Secondary Voltage	277
Secondary Max Current	<u>31.3A</u>
Secondary Markings	<u>X1-X2-X3</u>
Secondary Terminals	Terminal Blocks
Primary Taps	N/A
Conductor Material	<u>Copper</u>
Insulation Class	<u>220°C (Class H)</u>
BIL (Insulation) Level	<u>10kV</u>
Efficiency (@35% Load) %	<u>N/A</u>
Impedance Range	<u>1.0 – 3.0%</u>
Sound (db)	<u>40</u>
Enclosure Type	NEMA 1
Enclosure Size	<u>E1-3</u>
Finish/Colour	Polyester Powder Coat – ANSI/ASA 61 Grey
Standards & Certifications	<u>CSA Certified File No. LR34493, UL Listed File No. E108255, ISO 9001:2015</u> Registered



**OFFICIAL QUOTE** 

#### 15KVA 440 VOLTS TO 277 VOLTS THREE PHASE AUTOTRANSFORMER



Country/Manufacturer

Canada/RPM