




15KVA 460 VOLTS TO 277 VOLTS SINGLE PHASE AUTOTRANSFORMER

\$1,587.50 CAD



Single Phase Autotransformer with a capacity of
15kVA, transforming 460 Volts to 277 Volts

SKU: MC15H1-D

Categories: [Autotransformers](#)



SCHEMATIC/DIAGRAM AND DIMENSION PICTURES



Single Phase Autotransformer with a capacity of 15kVA, transforming 460 Volts to 277 Volts



PRODUCT SPECIFICATIONS

Weight	91.3 lbs
Phases	1
kVA	15
Connection	1PhA-NT-1
Primary Voltage	460
Primary Max Current	18.8A
Primary Markings	H0-H1
Primary Terminals	Terminal Blocks
Secondary Voltage	277
Secondary Max Current	31.3A
Secondary Markings	X0-X1
Secondary Terminals	Terminal Blocks
Primary Taps	N/A
Conductor Material	Copper
Insulation Class	220°C (Class H)
BIL (Insulation) Level	10kV
Efficiency (@35% Load) %	N/A
Impedance Range	1.0 – 3.0%
Sound (db)	40 dB
Enclosure Type	NEMA 1
Enclosure Size	E1-2
Finish/Colour	Polyester Powder Coat – ANSI/ASA 61 Grey
Standards & Certifications	CSA Certified File No. LR34493, UL Listed File No. E108255, ISO 9001:2015 Registered



OFFICIAL QUOTE

15KVA 460 VOLTS TO 277 VOLTS

SINGLE PHASE AUTOTRANSFORMER



Country/Manufacturer	Canada/RPM
----------------------	----------------------------