

OFFICIAL QUOTE

15KVA 550 VOLTS TO 277 VOLTS THREE PHASE AUTOTRANSFORMER





15KVA 550 VOLTS TO 277 VOLTS THREE PHASE AUTOTRANSFORMER


\$2,347.20 CAD

Three Phase Autotransformer with a capacity of 15kVA, transforming 550Y Volts to 277Y Volts

SKU: RC15J2-D

Categories: <u>Autotransformer</u>

SCHEMATIC/DIAGRAM AND DIMENSION PICTURES





Three Phase Autotransformer with a capacity of 15kVA, transforming 550Y Volts to 277Y Volts



OFFICIAL QUOTE



15KVA 550 VOLTS TO 277 VOLTS THREE PHASE AUTOTRANSFORMER

PRODUCT SPECIFICATIONS

PRODUCT SPECIFICATIONS	
Weight	54 lbs
Phases	<u>3</u>
kVA	<u>15</u>
Connection	3PhA-NT-1
Primary Voltage	<u>550</u>
Primary Max Current	<u>15.7A</u>
Primary Markings	<u>H1-H2-H3</u>
Primary Terminals	<u>Terminal Blocks</u>
Secondary Voltage	277
Secondary Max Current	31.3A
Secondary Markings	<u>X1-X2-X3</u>
Secondary Terminals	Terminal Blocks
Primary Taps	N/A
Conductor Material	Copper
Insulation Class	220°C (Class H)
BIL (Insulation) Level	<u>10kV</u>
Efficiency (@35% Load) %	N/A
Impedance Range	1.5 - 3.5%
Sound (db)	40
Enclosure Type	NEMA 1
Enclosure Size	<u>E1-3</u>
Finish/Colour	Polyester Powder Coat - ANSI/ASA 61 Grey
Standards & Certifications	CSA Certified File No. LR34493, UL Listed File No. E108255, ISO 9001:2015 Registered



OFFICIAL QUOTE

15KVA 550 VOLTS TO 277 VOLTS THREE PHASE AUTOTRANSFORMER



Country/Manufacturer	Canada/RPM
----------------------	------------