




200KVA 380 VOLTS TO 277 VOLTS SINGLE PHASE AUTOTRANSFORMER



\$6,498.10 CAD

Single Phase Autotransformer with a capacity of 200kVA, transforming 380 Volts to 277 Volts

SKU: MC200F-D

Categories: [Autotransformers](#)

SCHEMATIC/DIAGRAM AND DIMENSION PICTURES



Single Phase Autotransformer with a capacity of 200kVA, transforming 380 Volts to 277 Volts



PRODUCT SPECIFICATIONS

Weight	463.1 lbs
Phases	1
kVA	200
Connection	1PhA-NT-1
Primary Voltage	380
Primary Max Current	303.9A
Primary Markings	H0-H1
Primary Terminals	Pads
Secondary Voltage	277
Secondary Max Current	416.9A
Secondary Markings	X0-X1
Secondary Terminals	Pads
Primary Taps	N/A
Conductor Material	Copper
Insulation Class	220°C (Class H)
BIL (Insulation) Level	10kV
Efficiency (@35% Load) %	N/A
Impedance Range	1.0 – 3.0%
Sound (db)	55 dB
Enclosure Type	NEMA 3R Indoor
Enclosure Size	E3R-7
Finish/Colour	Polyester Powder Coat – ANSI/ASA 61 Grey
Standards & Certifications	CSA Certified File No. LR34493, UL Listed File No. E108255, ISO 9001:2015 Registered



OFFICIAL QUOTE

200KVA 380 VOLTS TO 277 VOLTS
SINGLE PHASE AUTOTRANSFORMER



Country/Manufacturer	Canada/RPM
----------------------	----------------------------