



225KVA 120 VOLTS TO 230 VOLTS THREE PHASE AUTOTRANSFORMER


\$9,237.20 CAD

Three Phase Autotransformer with a capacity of 225kVA, transforming 120Y Volts to 230Y Volts

SKU: RA225A-C1

Categories: [Autotransformers](#)

SCHEMATIC/DIAGRAM AND DIMENSION PICTURES



Three Phase Autotransformer with a capacity of 225kVA, transforming 120Y Volts to 230Y Volts



PRODUCT SPECIFICATIONS

Weight	730 lbs
Phases	3
kVA	225
Connection	3PhA-NT-1
Primary Voltage	120
Primary Max Current	1082.5A
Primary Markings	X1-X2-X3
Primary Terminals	Pads
Secondary Voltage	230
Secondary Max Current	564.8A
Secondary Markings	H1-H2-H3
Secondary Terminals	Pads
Primary Taps	N/A
Conductor Material	Aluminum
Insulation Class	220°C (Class H)
BIL (Insulation) Level	10kV
Efficiency (@35% Load) %	N/A
Impedance Range	1.5 – 3.5%
Sound (db)	55
Enclosure Type	NEMA 3R Indoor
Enclosure Size	E3R-8
Finish/Colour	Polyester Powder Coat – ANSI/ASA 61 Grey
Standards & Certifications	CSA Certified File No. LR34493, UL Listed File No. E108255, ISO 9001:2015 Registered



OFFICIAL QUOTE

225KVA 120 VOLTS TO 230 VOLTS
THREE PHASE AUTOTRANSFORMER



Country/Manufacturer

[Canada/RPM](#)