



OFFICIAL QUOTE

225KVA 220 VOLTS TO 460 VOLTS THREE PHASE AUTOTRANSFORMER



225KVA 220 VOLTS TO 460 VOLTS THREE PHASE AUTOTRANSFORMER

\$13,620.40 CAD

Three Phase Autotransformer with a capacity of 225kVA, transforming 220Y Volts to 460Y Volts

SKU: RC225C2-H1

Categories: [Autotransformers](#)

SCHEMATIC/DIAGRAM AND DIMENSION PICTURES



Three Phase Autotransformer with a capacity of 225kVA, transforming 220Y Volts to 460Y Volts



OFFICIAL QUOTE

225KVA 220 VOLTS TO 460 VOLTS THREE PHASE AUTOTRANSFORMER



PRODUCT SPECIFICATIONS

Weight	1077 lbs
Phases	3
kVA	225
Connection	3PhA-NT-1
Primary Voltage	220
Primary Max Current	590.5A
Primary Markings	X1-X2-X3
Primary Terminals	Pads
Secondary Voltage	460
Secondary Max Current	282.4A
Secondary Markings	H1-H2-H3
Secondary Terminals	Pads
Primary Taps	N/A
Conductor Material	Copper
Insulation Class	220°C (Class H)
BIL (Insulation) Level	10kV
Efficiency (@35% Load) %	N/A
Impedance Range	1.5 – 3.5%
Sound (db)	55
Enclosure Type	NEMA 3R Indoor
Enclosure Size	E3R-8
Finish/Colour	Polyester Powder Coat – ANSI/ASA 61 Grey
Standards & Certifications	CSA Certified File No. LR34493, UL Listed File No. E108255, ISO 9001:2015 Registered



OFFICIAL QUOTE

225KVA 220 VOLTS TO 460 VOLTS
THREE PHASE AUTOTRANSFORMER



Country/Manufacturer

[Canada/RPM](#)