

#### **OFFICIAL QUOTE**

### 225KVA 277 VOLTS TO 575 VOLTS THREE PHASE AUTOTRANSFORMER





### 225KVA 277 VOLTS TO 575 VOLTS THREE PHASE AUTOTRANSFORMER


\$13,529.50 CAD


Three Phase Autotransformer with a capacity of 225kVA, transforming 277Y Volts to 575Y Volts

**SKU:** RC225D-J1

**Categories:** Autotransformer

#### SCHEMATIC/DIAGRAM AND DIMENSION PICTURES





Three Phase Autotransformer with a capacity of 225kVA, transforming 277Y Volts to 575Y Volts



### **OFFICIAL QUOTE**

# 225KVA 277 VOLTS TO 575 VOLTS THREE PHASE AUTOTRANSFORMER



### **PRODUCT SPECIFICATIONS**

Weight	1068 lbs
Phases	<u>3</u>
kVA	225
Connection	3PhA-NT-1
Primary Voltage	120/240
Primary Max Current	469A
Primary Markings	<u>X1-X2-X3</u>
Primary Terminals	<u>Pads</u>
Secondary Voltage	<u>575</u>
Secondary Max Current	225.9A
Secondary Markings	H1-H2-H3
Secondary Terminals	600MCM-2
Primary Taps	N/A
Conductor Material	<u>Copper</u>
Insulation Class	220°C (Class H)
BIL (Insulation) Level	<u>10kV</u>
Efficiency (@35% Load) %	N/A
Impedance Range	<u>1.5 – 3.5%</u>
Sound (db)	<u>55</u>
Enclosure Type	NEMA 3R Indoor
Enclosure Size	<u>E3R-8</u>
Finish/Colour	Polyester Powder Coat – ANSI/ASA 61 Grey
Standards & Certifications	CSA Certified File No. LR34493, UL Listed File No. E108255, ISO 9001:2015 Registered



### **OFFICIAL QUOTE**

# 225KVA 277 VOLTS TO 575 VOLTS THREE PHASE AUTOTRANSFORMER



Country/Manufacturer	Canada/RPM
----------------------	------------