



225KVA 400 VOLTS TO 550 VOLTS THREE PHASE AUTOTRANSFORMER

\$5,900.30 CAD

Three Phase Autotransformer with a capacity of 225kVA, transforming 400Y Volts to 550Y Volts

SKU: RA225G1-J2

Categories: [Autotransformers](#)

SCHEMATIC/DIAGRAM AND DIMENSION PICTURES



Three Phase Autotransformer with a capacity of 225kVA, transforming 400Y Volts to 550Y Volts



PRODUCT SPECIFICATIONS

| | |
|---------------------------------------|--|
| Weight | 383 lbs |
| Phases | 3 |
| kVA | 225 |
| Connection | 3PhA-NT-1 |
| Primary Voltage | 400 |
| Primary Max Current | 324.8A |
| Primary Markings | X1-X2-X3 |
| Primary Terminals | Pads |
| Secondary Voltage | 550 |
| Secondary Max Current | 236.2A |
| Secondary Markings | H1-H2-H3 |
| Secondary Terminals | 600MCM-2 |
| Primary Taps | N/A |
| Conductor Material | Aluminum |
| Insulation Class | 220°C (Class H) |
| BIL (Insulation) Level | 10kV |
| Efficiency (@35% Load) % | N/A |
| Impedance Range | 1.0 – 3.0% |
| Sound (db) | 55 |
| Enclosure Type | NEMA 3R Indoor |
| Enclosure Size | E3R-7 |
| Finish/Colour | Polyester Powder Coat – ANSI/ASA 61 Grey |
| Standards & Certifications | CSA Certified File No. LR34493, UL Listed File No. E108255, ISO 9001:2015 Registered |



OFFICIAL QUOTE

225KVA 400 VOLTS TO 550 VOLTS
THREE PHASE AUTOTRANSFORMER



Country/Manufacturer

[Canada/RPM](#)