

#### **OFFICIAL QUOTE**

### 225KVA 440 VOLTS TO 115 VOLTS THREE PHASE AUTOTRANSFORMER





### 225KVA 440 VOLTS TO 115 VOLTS THREE PHASE AUTOTRANSFORMER

\$18,898.60 CAD

Three Phase Autotransformer with a capacity of 225kVA, transforming 440Y Volts to 115Y Volts

SKU: RC225H2-A1

**Categories:** Autotransformer

#### SCHEMATIC/DIAGRAM AND DIMENSION PICTURES





Three Phase Autotransformer with a capacity of 225kVA, transforming 440Y Volts to 115Y Volts



### **OFFICIAL QUOTE**



# 225KVA 440 VOLTS TO 115 VOLTS THREE PHASE AUTOTRANSFORMER

### **PRODUCT SPECIFICATIONS**

Weight	1460 lbs
Phases	3
kVA	225
Connection	3PhA-NT-1
Primary Voltage	440
Primary Max Current	295.2A
Primary Markings	H1-H2-H3
Primary Terminals	Pads
Secondary Voltage	115
Secondary Max Current	1129.6A
Secondary Markings	X1-X2-X3
Secondary Terminals	Pads
Primary Taps	N/A
Conductor Material	Copper
Insulation Class	220°C (Class H)
BIL (Insulation) Level	10kV
Efficiency (@35% Load) %	N/A
Impedance Range	<u>2.5 – 4.5%</u>
Sound (db)	<u>60</u>
Enclosure Type	NEMA 3R Indoor
Enclosure Size	<u>E3R-8</u>
Finish/Colour	Polyester Powder Coat - ANSI/ASA 61 Grey
Standards & Certifications	CSA Certified File No. LR34493, UL Listed File No. E108255, ISO 9001:2015 Registered



### **OFFICIAL QUOTE**

## 225KVA 440 VOLTS TO 115 VOLTS THREE PHASE AUTOTRANSFORMER



Country/Manufacturer	Canada/RPM
----------------------	------------