




225KVA 575 VOLTS TO 380 VOLTS SINGLE PHASE AUTOTRANSFORMER



\$8,377.90 CAD

Single Phase Autotransformer with a capacity of 225kVA, transforming 575 Volts to 380 Volts

SKU: MC225J1-F

Categories: [Autotransformer](#)

SCHEMATIC/DIAGRAM AND DIMENSION PICTURES



Single Phase Autotransformer with a capacity of 225kVA, transforming 575 Volts to 380 Volts



PRODUCT SPECIFICATIONS

Weight	624.4 lbs
Phases	1
kVA	225
Connection	1PhA-NT-1
Primary Voltage	575
Primary Max Current	225.9A
Primary Markings	H0-H1
Primary Terminals	600MCM-2
Secondary Voltage	380
Secondary Max Current	341.9A
Secondary Markings	X0-X1
Secondary Terminals	Pads
Primary Taps	N/A
Conductor Material	Copper
Insulation Class	220°C (Class H)
BIL (Insulation) Level	10kV
Efficiency (@35% Load) %	N/A
Impedance Range	1.0 – 3.0%
Sound (db)	55 dB
Enclosure Type	NEMA 3R Indoor
Enclosure Size	E3R-8S
Finish/Colour	Polyester Powder Coat – ANSI/ASA 61 Grey
Standards & Certifications	CSA Certified File No. LR34493, UL Listed File No. E108255, ISO 9001:2015 Registered



OFFICIAL QUOTE

225KVA 575 VOLTS TO 380 VOLTS
SINGLE PHASE AUTOTRANSFORMER



Country/Manufacturer	Canada/RPM
----------------------	----------------------------