



OFFICIAL QUOTE

2500KVA 220 VOLTS TO 200 VOLTS THREE PHASE AUTOTRANSFORMER



2500KVA 220 VOLTS TO 200 VOLTS THREE PHASE AUTOTRANSFORMER

\$25,325.70 CAD

Three Phase Autotransformer with a capacity of 2500kVA, transforming 220Y Volts to 200Y Volts

SKU: RA2500C2-B1

Categories: [Autotransformers](#)

SCHEMATIC/DIAGRAM AND DIMENSION PICTURES



Three Phase Autotransformer with a capacity of 2500kVA, transforming 220Y Volts to 200Y Volts



OFFICIAL QUOTE

2500KVA 220 VOLTS TO 200 VOLTS
THREE PHASE AUTOTRANSFORMER

PRODUCT SPECIFICATIONS

Weight	1569 lbs
Phases	3
kVA	2500
Connection	3PhA-NT-1
Primary Voltage	220
Primary Max Current	6560.8A
Primary Markings	H1-H2-H3
Primary Terminals	Pads
Secondary Voltage	200
Secondary Max Current	7216.9A
Secondary Markings	X1-X2-X3
Secondary Terminals	Pads
Primary Taps	N/A
Conductor Material	Aluminum
Insulation Class	220°C (Class H)
BIL (Insulation) Level	10kV
Efficiency (@35% Load) %	N/A
Impedance Range	0.5 – 1.5%
Sound (db)	60
Enclosure Type	NEMA 3R Indoor
Enclosure Size	E3R-9
Finish/Colour	Polyester Powder Coat – ANSI/ASA 61 Grey
Standards & Certifications	CSA Certified File No. LR34493, UL Listed File No. E108255, ISO 9001:2015 Registered



OFFICIAL QUOTE

2500KVA 220 VOLTS TO 200 VOLTS
THREE PHASE AUTOTRANSFORMER



Country/Manufacturer

[Canada/RPM](#)