



25KVA 600 VOLTS TO 220 VOLTS SINGLE PHASE AUTOTRANSFORMER

\$2,777.50 CAD

Single Phase Autotransformer with a capacity of 25kVA, transforming 600 Volts to 220 Volts

SKU: MC25J-C2

Categories: [Autotransformers](#)

SCHEMATIC/DIAGRAM AND DIMENSION PICTURES



Single Phase Autotransformer with a capacity of 25kVA, transforming 600 Volts to 220 Volts



PRODUCT SPECIFICATIONS

Weight	163.1 lbs
Phases	1
kVA	25
Connection	1PhA-NT-1
Primary Voltage	600
Primary Max Current	24.1A
Primary Markings	H0-H1
Primary Terminals	Terminal Blocks
Secondary Voltage	220
Secondary Max Current	65.6A
Secondary Markings	X0-X1
Secondary Terminals	#2-14 AWG
Primary Taps	N/A
Conductor Material	Copper
Insulation Class	220°C (Class H)
BIL (Insulation) Level	10kV
Efficiency (@35% Load) %	N/A
Impedance Range	2.5 – 4.5%
Sound (db)	45 dB
Enclosure Type	NEMA 3R Indoor
Enclosure Size	E3R-4
Finish/Colour	Polyester Powder Coat – ANSI/ASA 61 Grey
Standards & Certifications	CSA Certified File No. LR34493, UL Listed File No. E108255, ISO 9001:2015 Registered



OFFICIAL QUOTE

25KVA 600 VOLTS TO 220 VOLTS
SINGLE PHASE AUTOTRANSFORMER



Country/Manufacturer	Canada/RPM
----------------------	----------------------------