

#### **OFFICIAL QUOTE**

## 300KVA 415 VOLTS TO 600 VOLTS THREE PHASE AUTOTRANSFORMER





## 300KVA 415 VOLTS TO 600 VOLTS THREE PHASE AUTOTRANSFORMER


\$11,396.00 CAD


Three Phase Autotransformer with a capacity of 300kVA, transforming 415Y Volts to 600Y Volts

**SKU:** RC300G2-J

**Categories:** Autotransformer

#### SCHEMATIC/DIAGRAM AND DIMENSION PICTURES





Three Phase Autotransformer with a capacity of 300kVA, transforming 415Y Volts to 600Y Volts



### **OFFICIAL QUOTE**

## 300KVA 415 VOLTS TO 600 VOLTS THREE PHASE AUTOTRANSFORMER



### **PRODUCT SPECIFICATIONS**

PRODUCT SPECIFICATIONS	
Weight	818 lbs
Phases	<u>3</u>
kVA	300
Connection	3PhA-NT-1
Primary Voltage	415
Primary Max Current	<u>417.4A</u>
Primary Markings	<u>X1-X2-X3</u>
Primary Terminals	<u>Pads</u>
Secondary Voltage	600
Secondary Max Current	288.7A
Secondary Markings	<u>H1-H2-H3</u>
Secondary Terminals	Pads
Primary Taps	N/A
Conductor Material	Copper
Insulation Class	220°C (Class H)
BIL (Insulation) Level	<u>10kV</u>
Efficiency (@35% Load) %	N/A
Impedance Range	1.0 - 3.0%
Sound (db)	<u>55</u>
Enclosure Type	NEMA 3R Indoor
Enclosure Size	<u>E3R-8</u>
Finish/Colour	Polyester Powder Coat – ANSI/ASA 61 Grey
Standards & Certifications	CSA Certified File No. LR34493, UL Listed File No. E108255, ISO 9001:2015  Registered



### **OFFICIAL QUOTE**

# 300KVA 415 VOLTS TO 600 VOLTS THREE PHASE AUTOTRANSFORMER



Country/Manufacturer	<u>Canada/RPM</u>
----------------------	-------------------