

OFFICIAL QUOTE

300KVA 440 VOLTS TO 415 VOLTS THREE PHASE AUTOTRANSFORMER





300KVA 440 VOLTS TO 415 VOLTS THREE PHASE AUTOTRANSFORMER


\$2,992.30 CAD

Three Phase Autotransformer with a capacity of 300kVA, transforming 440Y Volts to 415Y Volts

SKU: RC300H2-G2

Categories: Autotransformer

SCHEMATIC/DIAGRAM AND DIMENSION PICTURES





Three Phase Autotransformer with a capacity of 300kVA, transforming 440Y Volts to 415Y Volts



OFFICIAL QUOTE 300KVA 440 VOLTS TO 415 VOLTS THREE PHASE AUTOTRANSFORMER



PRODUCT SPECIFICATIONS

Weight	140 lbs
Phases	3
kVA	300
Connection	<u>3PhA-NT-1</u>
Primary Voltage	440
Primary Max Current	<u>393.6A</u>
Primary Markings	H1-H2-H3
Primary Terminals	<u>Pads</u>
Secondary Voltage	415
Secondary Max Current	417.4A
Secondary Markings	<u>X1-X2-X3</u>
Secondary Terminals	<u>Pads</u>
Primary Taps	N/A
Conductor Material	Copper
Insulation Class	220°C (Class H)
BIL (Insulation) Level	<u>10kV</u>
Efficiency (@35% Load) %	N/A
Impedance Range	0.5 – 1.5%
Sound (db)	<u>45</u>
Enclosure Type	NEMA 3R Indoor
Enclosure Size	<u>E3R-5</u>
Finish/Colour	Polyester Powder Coat - ANSI/ASA 61 Grey
Standards & Certifications	CSA Certified File No. LR34493, UL Listed File No. E108255, ISO 9001:2015 Registered



OFFICIAL QUOTE

300KVA 440 VOLTS TO 415 VOLTS THREE PHASE AUTOTRANSFORMER



Country/Manufacturer	<u>Canada/RPM</u>
----------------------	-------------------