


OFFICIAL QUOTE

30KVA 208 VOLTS TO 220 VOLTS THREE PHASE AUTOTRANSFORMER





30KVA 208 VOLTS TO 220 VOLTS THREE PHASE AUTOTRANSFORMER

\$1,286.60 CAD

Three Phase Autotransformer with a capacity of 30kVA, transforming 208Y Volts to 220Y Volts

SKU: RC30B-C2 Categories: <u>Autotransformer</u>

SCHEMATIC/DIAGRAM AND DIMENSION PICTURES





Three Phase Autotransformer with a capacity of 30kVA, transforming 208Y Volts to 220Y Volts



OFFICIAL QUOTE

30KVA 208 VOLTS TO 220 VOLTS THREE PHASE AUTOTRANSFORMER



PRODUCT SPECIFICATIONS

| Weight | 20 lbs |
|----------------------------|---|
| Phases | <u>3</u> |
| kVA | <u>30</u> |
| Connection | <u>3PhA-NT-1</u> |
| Primary Voltage | 208 |
| Primary Max Current | <u>83.3A</u> |
| Primary Markings | <u>X1-X2-X3</u> |
| Primary Terminals | <u>#2/0-6 AWG</u> |
| Secondary Voltage | 220 |
| Secondary Max Current | <u>78.7A</u> |
| Secondary Markings | <u>H1-H2-H3</u> |
| Secondary Terminals | <u>#2/0-6 AWG</u> |
| Primary Taps | N/A |
| Conductor Material | <u>Copper</u> |
| Insulation Class | <u>180°C (Class F)</u> |
| BIL (Insulation) Level | <u>10kV</u> |
| Efficiency (@35% Load) % | <u>N/A</u> |
| Impedance Range | <u>0.5 – 1.5%</u> |
| Sound (db) | <u>40</u> |
| Enclosure Type | NEMA 1 |
| Enclosure Size | <u>E1-1</u> |
| Finish/Colour | Polyester Powder Coat – ANSI/ASA 61 Grey |
| Standards & Certifications | <u>CSA Certified File No. LR34493, UL Listed File No. E108255, ISO 9001:2015</u> <u>Registered</u> |



OFFICIAL QUOTE

30KVA 208 VOLTS TO 220 VOLTS THREE PHASE AUTOTRANSFORMER



Country/Manufacturer

Canada/RPM