


OFFICIAL QUOTE

30KVA 440 VOLTS TO 415 VOLTS THREE PHASE AUTOTRANSFORMER





30KVA 440 VOLTS TO 415 VOLTS THREE PHASE AUTOTRANSFORMER


\$1,311.10 CAD

Three Phase Autotransformer with a capacity of 30kVA, transforming 440Y Volts to 415Y Volts

SKU: RC30H2-G2

Categories: Autotransformer

SCHEMATIC/DIAGRAM AND DIMENSION PICTURES





Three Phase Autotransformer with a capacity of 30kVA, transforming 440Y Volts to 415Y Volts



OFFICIAL QUOTE



30KVA 440 VOLTS TO 415 VOLTS THREE PHASE AUTOTRANSFORMER

PRODUCT SPECIFICATIONS

Weight	20 lbs
Phases	<u>3</u>
kVA	30
Connection	3PhA-NT-1
Primary Voltage	440
Primary Max Current	<u>39.4A</u>
Primary Markings	<u>H1-H2-H3</u>
Primary Terminals	#2-14 AWG
Secondary Voltage	415
Secondary Max Current	41.7A
Secondary Markings	<u>X1-X2-X3</u>
Secondary Terminals	#2-14 AWG
Primary Taps	N/A
Conductor Material	Copper
Insulation Class	180°C (Class F)
BIL (Insulation) Level	10kV
Efficiency (@35% Load) %	N/A
Impedance Range	0.5 - 1.5%
Sound (db)	40
Enclosure Type	NEMA 1
Enclosure Size	<u>E1-1</u>
Finish/Colour	Polyester Powder Coat - ANSI/ASA 61 Grey
Standards & Certifications	CSA Certified File No. LR34493, UL Listed File No. E108255, ISO 9001:2015 Registered



OFFICIAL QUOTE

30KVA 440 VOLTS TO 415 VOLTS THREE PHASE AUTOTRANSFORMER



Country/Manufacturer	Canada/RPM
----------------------	------------