



OFFICIAL QUOTE

37.5KVA 277 VOLTS TO 440 VOLTS SINGLE PHASE AUTOTRANSFORMER



37.5KVA 277 VOLTS TO 440 VOLTS SINGLE PHASE AUTOTRANSFORMER


\$2,534.00 CAD

Single Phase Autotransformer with a capacity of 37.5kVA, transforming 277 Volts to 440 Volts

SKU: MC37D-H2

Categories: [Autotransformers](#)

SCHEMATIC/DIAGRAM AND DIMENSION PICTURES



Single Phase Autotransformer with a capacity of 37.5kVA, transforming 277 Volts to 440 Volts



OFFICIAL QUOTE

37.5KVA 277 VOLTS TO 440 VOLTS
SINGLE PHASE AUTOTRANSFORMER

PRODUCT SPECIFICATIONS

Weight	151.2 lbs
Phases	1
kVA	37.5
Connection	1PhA-NT-1
Primary Voltage	277
Primary Max Current	78.2A
Primary Markings	X0-X1
Primary Terminals	#2/0-6 AWG
Secondary Voltage	440
Secondary Max Current	49.2A
Secondary Markings	H0-H1
Secondary Terminals	#2-14 AWG
Primary Taps	N/A
Conductor Material	Copper
Insulation Class	220°C (Class H)
BIL (Insulation) Level	10kV
Efficiency (@35% Load) %	N/A
Impedance Range	1.0 – 3.0%
Sound (db)	45 dB
Enclosure Type	NEMA 3R Indoor
Enclosure Size	E3R-4
Finish/Colour	Polyester Powder Coat – ANSI/ASA 61 Grey
Standards & Certifications	CSA Certified File No. LR34493, UL Listed File No. E108255, ISO 9001:2015 Registered



OFFICIAL QUOTE

37.5KVA 277 VOLTS TO 440 VOLTS
SINGLE PHASE AUTOTRANSFORMER



Country/Manufacturer

[Canada/RPM](#)