




37.5KVA 440 VOLTS TO 416 VOLTS SINGLE PHASE AUTOTRANSFORMER



\$901.60 CAD

Single Phase Autotransformer with a capacity of 37.5kVA, transforming 440 Volts to 416 Volts

SKU: MC37H2-G

Categories: [Autotransformers](#)

SCHEMATIC/DIAGRAM AND DIMENSION PICTURES



Single Phase Autotransformer with a capacity of 37.5kVA, transforming 440 Volts to 416 Volts



PRODUCT SPECIFICATIONS

Weight	66.7 lbs
Phases	1
kVA	37.5
Connection	1PhA-NT-1
Primary Voltage	440
Primary Max Current	49.2A
Primary Markings	H0-H1
Primary Terminals	#2-14 AWG
Secondary Voltage	416
Secondary Max Current	52A
Secondary Markings	X0-X1
Secondary Terminals	#2-14 AWG
Primary Taps	N/A
Conductor Material	Copper
Insulation Class	180°C (Class F)
BIL (Insulation) Level	10kV
Efficiency (@35% Load) %	N/A
Impedance Range	0.5 – 1.5%
Sound (db)	40 dB
Enclosure Type	NEMA 1
Enclosure Size	E1-0
Finish/Colour	Polyester Powder Coat – ANSI/ASA 61 Grey
Standards & Certifications	CSA Certified File No. LR34493, UL Listed File No. E108255, ISO 9001:2015 Registered



OFFICIAL QUOTE

37.5KVA 440 VOLTS TO 416 VOLTS
SINGLE PHASE AUTOTRANSFORMER



Country/Manufacturer	Canada/RPM
----------------------	----------------------------