


OFFICIAL QUOTE

45KVA 120 VOLTS TO 220 VOLTS THREE PHASE AUTOTRANSFORMER





45KVA 120 VOLTS TO 220 VOLTS THREE PHASE AUTOTRANSFORMER


\$3,246.70 CAD

Three Phase Autotransformer with a capacity of 45kVA, transforming 120Y Volts to 220Y Volts

SKU: RC45A-C2

Categories: Autotransformer

SCHEMATIC/DIAGRAM AND DIMENSION PICTURES





Three Phase Autotransformer with a capacity of 45kVA, transforming 120Y Volts to 220Y Volts



OFFICIAL QUOTE

45KVA 120 VOLTS TO 220 VOLTS THREE PHASE AUTOTRANSFORMER



PRODUCT SPECIFICATIONS

| PRODUCT SPECIFICATIONS | |
|----------------------------|--|
| Weight | 174 lbs |
| Phases | <u>3</u> |
| kVA | 45 |
| Connection | <u>3PhA-NT-1</u> |
| Primary Voltage | 120 |
| Primary Max Current | 216.5A |
| Primary Markings | <u>X1-X2-X3</u> |
| Primary Terminals | 600MCM-2 |
| Secondary Voltage | 220 |
| Secondary Max Current | 118.1A |
| Secondary Markings | H1-H2-H3 |
| Secondary Terminals | 300MCM-6 |
| Primary Taps | N/A |
| Conductor Material | Copper |
| Insulation Class | 220°C (Class H) |
| BIL (Insulation) Level | <u>10kV</u> |
| Efficiency (@35% Load) % | N/A |
| Impedance Range | <u>1.5 – 3.5%</u> |
| Sound (db) | 45 |
| Enclosure Type | NEMA 3R Indoor |
| Enclosure Size | <u>E3R-5</u> |
| Finish/Colour | Polyester Powder Coat – ANSI/ASA 61 Grey |
| Standards & Certifications | CSA Certified File No. LR34493, UL Listed File No. E108255, ISO 9001:2015 Registered |



OFFICIAL QUOTE

45KVA 120 VOLTS TO 220 VOLTS THREE PHASE AUTOTRANSFORMER



| Country/Manufacturer | Canada/RPM |
|----------------------|------------|
|----------------------|------------|