




**45KVA 230 VOLTS TO 416 VOLTS
THREE PHASE AUTOTRANSFORMER**



**45KVA 230 VOLTS TO 416
VOLTS THREE PHASE
AUTOTRANSFORMER**

\$2,981.80 CAD

Three Phase Autotransformer with a capacity of 45kVA, transforming 230Y Volts to 416Y Volts

SKU: RA45C1-G

Categories: [Autotransformer](#)

SCHEMATIC/DIAGRAM AND DIMENSION PICTURES



Three Phase Autotransformer with a capacity of 45kVA, transforming 230Y Volts to 416Y Volts



PRODUCT SPECIFICATIONS

Weight	128 lbs
Phases	3
kVA	45
Connection	3PhA-NT-1
Primary Voltage	230
Primary Max Current	113A
Primary Markings	X1-X2-X3
Primary Terminals	300MCM-6
Secondary Voltage	416
Secondary Max Current	62.5A
Secondary Markings	H1-H2-H3
Secondary Terminals	#2-14 AWG
Primary Taps	N/A
Conductor Material	Aluminum
Insulation Class	220°C (Class H)
BIL (Insulation) Level	10kV
Efficiency (@35% Load) %	N/A
Impedance Range	1.5 – 3.5%
Sound (db)	45
Enclosure Type	NEMA 3R Indoor
Enclosure Size	E3R-5
Finish/Colour	Polyester Powder Coat – ANSI/ASA 61 Grey
Standards & Certifications	CSA Certified File No. LR34493, UL Listed File No. E108255, ISO 9001:2015 Registered



OFFICIAL QUOTE
45KVA 230 VOLTS TO 416 VOLTS
THREE PHASE AUTOTRANSFORMER



Country/Manufacturer

[Canada/RPM](#)