




**45KVA 277 VOLTS TO 480 VOLTS
THREE PHASE AUTOTRANSFORMER**



**45KVA 277 VOLTS TO 480
VOLTS THREE PHASE
AUTOTRANSFORMER**



\$3,000.20 CAD

Three Phase Autotransformer with a capacity of 45kVA, transforming 277Y Volts to 480Y Volts

SKU: RC45D-H

Categories: [Autotransformers](#)

SCHEMATIC/DIAGRAM AND DIMENSION PICTURES



Three Phase Autotransformer with a capacity of 45kVA, transforming 277Y Volts to 480Y Volts



OFFICIAL QUOTE

45KVA 277 VOLTS TO 480 VOLTS THREE PHASE AUTOTRANSFORMER



PRODUCT SPECIFICATIONS

Weight	160 lbs
Phases	3
kVA	45
Connection	3PhA-NT-1
Primary Voltage	277
Primary Max Current	93.8A
Primary Markings	X1-X2-X3
Primary Terminals	#2/0-6 AWG
Secondary Voltage	480
Secondary Max Current	54.1A
Secondary Markings	H1-H2-H3
Secondary Terminals	#2-14 AWG
Primary Taps	N/A
Conductor Material	Copper
Insulation Class	220°C (Class H)
BIL (Insulation) Level	10kV
Efficiency (@35% Load) %	N/A
Impedance Range	1.5 – 3.5%
Sound (db)	45
Enclosure Type	NEMA 3R Indoor
Enclosure Size	E3R-5
Finish/Colour	Polyester Powder Coat – ANSI/ASA 61 Grey
Standards & Certifications	CSA Certified File No. LR34493, UL Listed File No. E108255, ISO 9001:2015 Registered



OFFICIAL QUOTE



45KVA 277 VOLTS TO 480 VOLTS
THREE PHASE AUTOTRANSFORMER

Country/Manufacturer

[Canada/RPM](#)