



45KVA 347 VOLTS TO 550 VOLTS THREE PHASE AUTOTRANSFORMER

\$2,690.80 CAD

Three Phase Autotransformer with a capacity of 45kVA, transforming 347Y Volts to 550Y Volts

SKU: RC45E-J2

Categories: [Autotransformer](#)

SCHEMATIC/DIAGRAM AND DIMENSION PICTURES



Three Phase Autotransformer with a capacity of 45kVA, transforming 347Y Volts to 550Y Volts



PRODUCT SPECIFICATIONS

Weight	137 lbs
Phases	3
kVA	45
Connection	3PhA-NT-1
Primary Voltage	347
Primary Max Current	74.9A
Primary Markings	X1-X2-X3
Primary Terminals	#2/0-6 AWG
Secondary Voltage	380
Secondary Max Current	47.2A
Secondary Markings	H1-H2-H3
Secondary Terminals	#2-14 AWG
Primary Taps	N/A
Conductor Material	Copper
Insulation Class	220°C (Class H)
BIL (Insulation) Level	10kV
Efficiency (@35% Load) %	N/A
Impedance Range	1.0 – 3.0%
Sound (db)	45
Enclosure Type	NEMA 3R Indoor
Enclosure Size	E3R-5
Finish/Colour	Polyester Powder Coat – ANSI/ASA 61 Grey
Standards & Certifications	CSA Certified File No. LR34493, UL Listed File No. E108255, ISO 9001:2015 Registered



OFFICIAL QUOTE

45KVA 347 VOLTS TO 550 VOLTS
THREE PHASE AUTOTRANSFORMER



Country/Manufacturer	Canada/RPM
----------------------	----------------------------