


#### **OFFICIAL QUOTE**

## 45KVA 415 VOLTS TO 230 VOLTS THREE PHASE AUTOTRANSFORMER





# 45KVA 415 VOLTS TO 230 VOLTS THREE PHASE AUTOTRANSFORMER

\$2,970.60 CAD


Three Phase Autotransformer with a capacity of 45kVA, transforming 415Y Volts to 230Y Volts

**SKU:** RA45G2-C1

**Categories:** Autotransformer

#### **SCHEMATIC/DIAGRAM AND DIMENSION PICTURES**





Three Phase Autotransformer with a capacity of 45kVA, transforming 415Y Volts to 230Y Volts



## **OFFICIAL QUOTE**



## 45KVA 415 VOLTS TO 230 VOLTS THREE PHASE AUTOTRANSFORMER

#### PRODUCT SPECIFICATIONS

| PRODUCT SPECIFICATIONS     |  |
|----------------------------|--|
| Weight                     | 128 lbs  |
| Phases                     | <u>3</u>   |
| kVA                        | 45   |
| Connection                 | <u>3PhA-NT-1</u>   |
| Primary Voltage            | 415  |
| Primary Max Current        | 62.6A  |
| Primary Markings           | H1-H2-H3   |
| Primary Terminals          | #2-14 AWG  |
| Secondary Voltage          | 230  |
| Secondary Max Current      | <u>113A</u>  |
| Secondary Markings         | <u>X1-X2-X3</u>  |
| Secondary Terminals        | 300MCM-6   |
| Primary Taps               | N/A  |
| Conductor Material         | Aluminum   |
| Insulation Class           | 220°C (Class H)  |
| BIL (Insulation) Level     | <u>10kV</u>  |
| Efficiency (@35% Load) %   | N/A  |
| Impedance Range            | 1.5 - 3.5%   |
| Sound (db)                 | 45   |
| Enclosure Type             | NEMA 3R Indoor   |
| Enclosure Size             | <u>E3R-5</u>   |
| Finish/Colour              | Polyester Powder Coat - ANSI/ASA 61 Grey   |
| Standards & Certifications | CSA Certified File No. LR34493, UL Listed File No. E108255, ISO 9001:2015 Registered |



## **OFFICIAL QUOTE**

# 45KVA 415 VOLTS TO 230 VOLTS THREE PHASE AUTOTRANSFORMER



| Country/Manufacturer | Canada/RPM |
|----------------------|------------|
|----------------------|------------|