




OFFICIAL QUOTE

45KVA 416 VOLTS TO 400 VOLTS THREE PHASE AUTOTRANSFORMER



45KVA 416 VOLTS TO 400 VOLTS THREE PHASE AUTOTRANSFORMER



\$1,320.60 CAD

Three Phase Autotransformer with a capacity of 45kVA, transforming 416Y Volts to 400Y Volts

SKU: RC45G-G1

Categories: [Autotransformers](#)

SCHEMATIC/DIAGRAM AND DIMENSION PICTURES



Three Phase Autotransformer with a capacity of 45kVA, transforming 416Y Volts to 400Y Volts



OFFICIAL QUOTE

45KVA 416 VOLTS TO 400 VOLTS
THREE PHASE AUTOTRANSFORMER

PRODUCT SPECIFICATIONS

Weight	20 lbs
Phases	3
kVA	45
Connection	3PhA-NT-1
Primary Voltage	416
Primary Max Current	62.5A
Primary Markings	H1-H2-H3
Primary Terminals	#2-14 AWG
Secondary Voltage	400
Secondary Max Current	65A
Secondary Markings	X1-X2-X3
Secondary Terminals	#2-14 AWG
Primary Taps	N/A
Conductor Material	Copper
Insulation Class	180°C (Class F)
BIL (Insulation) Level	10kV
Efficiency (@35% Load) %	N/A
Impedance Range	0.5 – 1.5%
Sound (db)	40
Enclosure Type	NEMA 1
Enclosure Size	E1-1
Finish/Colour	Polyester Powder Coat – ANSI/ASA 61 Grey
Standards & Certifications	CSA Certified File No. LR34493, UL Listed File No. E108255, ISO 9001:2015 Registered



OFFICIAL QUOTE



45KVA 416 VOLTS TO 400 VOLTS
THREE PHASE AUTOTRANSFORMER

Country/Manufacturer

[Canada/RPM](#)