




45KVA 460 VOLTS TO 550 VOLTS THREE PHASE AUTOTRANSFORMER



\$2,329.80 CAD

Three Phase Autotransformer with a capacity of 45kVA, transforming 460Y Volts to 550Y Volts

SKU: RC45H1-J2

Categories: [Autotransformer](#)

SCHEMATIC/DIAGRAM AND DIMENSION PICTURES



Three Phase Autotransformer with a capacity of 45kVA, transforming 460Y Volts to 550Y Volts



PRODUCT SPECIFICATIONS

Weight	54 lbs
Phases	3
kVA	45
Connection	3PhA-NT-1
Primary Voltage	460
Primary Max Current	56.5A
Primary Markings	X1-X2-X3
Primary Terminals	#2-14 AWG
Secondary Voltage	380
Secondary Max Current	47.2A
Secondary Markings	H1-H2-H3
Secondary Terminals	#2-14 AWG
Primary Taps	N/A
Conductor Material	Copper
Insulation Class	220°C (Class H)
BIL (Insulation) Level	10kV
Efficiency (@35% Load) %	N/A
Impedance Range	0.5 – 1.5%
Sound (db)	40
Enclosure Type	NEMA 1
Enclosure Size	E1-3
Finish/Colour	Polyester Powder Coat – ANSI/ASA 61 Grey
Standards & Certifications	CSA Certified File No. LR34493, UL Listed File No. E108255, ISO 9001:2015 Registered



OFFICIAL QUOTE
45KVA 460 VOLTS TO 550 VOLTS
THREE PHASE AUTOTRANSFORMER



Country/Manufacturer

[Canada/RPM](#)