

OFFICIAL QUOTE

500KVA 415 VOLTS TO 240 VOLTS THREE PHASE AUTOTRANSFORMER





500KVA 415 VOLTS TO 240 VOLTS THREE PHASE AUTOTRANSFORMER


\$21,356.70 CAD

Three Phase Autotransformer with a capacity of 500kVA, transforming 415Y Volts to 240Y Volts

SKU: RC500G2-C Categories: <u>Autotransformer</u>

SCHEMATIC/DIAGRAM AND DIMENSION PICTURES





Three Phase Autotransformer with a capacity of 500kVA, transforming 415Y Volts to 240Y Volts



OFFICIAL QUOTE

500KVA 415 VOLTS TO 240 VOLTS THREE PHASE AUTOTRANSFORMER



PRODUCT SPECIFICATIONS

Weight	1919 lbs
Phases	<u>3</u>
kVA	500
Connection	<u>3PhA-NT-1</u>
Primary Voltage	<u>415</u>
Primary Max Current	<u>695.6A</u>
Primary Markings	<u>H1-H2-H3</u>
Primary Terminals	Pads
Secondary Voltage	240
Secondary Max Current	<u>1202.8A</u>
Secondary Markings	<u>X1-X2-X3</u>
Secondary Terminals	Pads
Primary Taps	N/A
Conductor Material	<u>Copper</u>
Insulation Class	<u>220°C (Class H)</u>
BIL (Insulation) Level	<u>10kV</u>
Efficiency (@35% Load) %	<u>N/A</u>
Impedance Range	<u>1.5 – 3.5%</u>
Sound (db)	<u>60</u>
Enclosure Type	NEMA 3R Indoor
Enclosure Size	<u>E3R-9</u>
Finish/Colour	Polyester Powder Coat – ANSI/ASA 61 Grey
Standards & Certifications	CSA Certified File No. LR34493, UL Listed File No. E108255, ISO 9001:2015 Registered



OFFICIAL QUOTE

500KVA 415 VOLTS TO 240 VOLTS THREE PHASE AUTOTRANSFORMER



Country/Manufacturer

Canada/RPM