

#### **OFFICIAL QUOTE**

## 500KVA 440 VOLTS TO 550 VOLTS THREE PHASE AUTOTRANSFORMER





# 500KVA 440 VOLTS TO 550 VOLTS THREE PHASE AUTOTRANSFORMER


\$12,320.00 CAD

Three Phase Autotransformer with a capacity of 500kVA, transforming 440Y Volts to 550Y Volts

**SKU:** RC500H2-J2

**Categories:** Autotransformer

#### SCHEMATIC/DIAGRAM AND DIMENSION PICTURES





Three Phase Autotransformer with a capacity of 500kVA, transforming 440Y Volts to 550Y Volts



## **OFFICIAL QUOTE**



# 500KVA 440 VOLTS TO 550 VOLTS THREE PHASE AUTOTRANSFORMER

#### PRODUCT SPECIFICATIONS

PRODUCT SPECIFICATIONS	
Weight	896 lbs
Phases	<u>3</u>
kVA	500
Connection	3PhA-NT-1
Primary Voltage	440
Primary Max Current	<u>656.1A</u>
Primary Markings	<u>X1-X2-X3</u>
Primary Terminals	<u>Pads</u>
Secondary Voltage	<u>550</u>
Secondary Max Current	<u>524.9A</u>
Secondary Markings	<u>H1-H2-H3</u>
Secondary Terminals	<u>Pads</u>
Primary Taps	N/A
Conductor Material	Copper
Insulation Class	220°C (Class H)
BIL (Insulation) Level	<u>10kV</u>
Efficiency (@35% Load) %	N/A
Impedance Range	0.5 - 1.5%
Sound (db)	<u>55</u>
Enclosure Type	NEMA 3R Indoor
Enclosure Size	<u>E3R-8</u>
Finish/Colour	Polyester Powder Coat - ANSI/ASA 61 Grey
Standards & Certifications	CSA Certified File No. LR34493, UL Listed File No. E108255, ISO 9001:2015 Registered



## **OFFICIAL QUOTE**

# 500KVA 440 VOLTS TO 550 VOLTS THREE PHASE AUTOTRANSFORMER



Country/Manufacturer	<u>Canada/RPM</u>
----------------------	-------------------