



5KVA 208 VOLTS TO 277 VOLTS SINGLE PHASE AUTOTRANSFORMER

\$764.10 CAD

Single Phase Autotransformer with a capacity of
5kVA, transforming 208 Volts to 277 Volts

SKU: MC5B-D

Categories: [Autotransformers](#)

SCHEMATIC/DIAGRAM AND DIMENSION PICTURES



Single Phase Autotransformer with a capacity of 5kVA, transforming 208 Volts to 277 Volts



PRODUCT SPECIFICATIONS

Weight	56.1 lbs
Phases	1
kVA	5
Connection	1PhA-NT-1
Primary Voltage	208
Primary Max Current	13.9A
Primary Markings	X0-X1
Primary Terminals	Terminal Blocks
Secondary Voltage	277
Secondary Max Current	10.4A
Secondary Markings	H0-H1
Secondary Terminals	Terminal Blocks
Primary Taps	N/A
Conductor Material	Copper
Insulation Class	180°C (Class F)
BIL (Insulation) Level	10kV
Efficiency (@35% Load) %	N/A
Impedance Range	1.0 – 3.0%
Sound (db)	40 dB
Enclosure Type	NEMA 1
Enclosure Size	E1-0
Finish/Colour	Polyester Powder Coat – ANSI/ASA 61 Grey
Standards & Certifications	CSA Certified File No. LR34493, UL Listed File No. E108255, ISO 9001:2015 Registered



OFFICIAL QUOTE

5KVA 208 VOLTS TO 277 VOLTS
SINGLE PHASE AUTOTRANSFORMER



Country/Manufacturer	Canada/RPM
----------------------	----------------------------