



5KVA 400 VOLTS TO 440 VOLTS SINGLE PHASE AUTOTRANSFORMER

\$628.10 CAD

Single Phase Autotransformer with a capacity of 5kVA, transforming 400 Volts to 440 Volts

SKU: MC5G1-H2

Categories: [Autotransformers](#)

SCHEMATIC/DIAGRAM AND DIMENSION PICTURES



Single Phase Autotransformer with a capacity of 5kVA, transforming 400 Volts to 440 Volts



PRODUCT SPECIFICATIONS

Weight	50.5 lbs
Phases	1
kVA	5
Connection	1PhA-NT-1
Primary Voltage	400
Primary Max Current	7.2A
Primary Markings	X0-X1
Primary Terminals	Terminal Blocks
Secondary Voltage	440
Secondary Max Current	6.6A
Secondary Markings	H0-H1
Secondary Terminals	Terminal Blocks
Primary Taps	N/A
Conductor Material	Copper
Insulation Class	180°C (Class F)
BIL (Insulation) Level	10kV
Efficiency (@35% Load) %	N/A
Impedance Range	0.5 – 1.5%
Sound (db)	40 dB
Enclosure Type	NEMA 1
Enclosure Size	E1-0
Finish/Colour	Polyester Powder Coat – ANSI/ASA 61 Grey
Standards & Certifications	CSA Certified File No. LR34493, UL Listed File No. E108255, ISO 9001:2015 Registered



OFFICIAL QUOTE

5KVA 400 VOLTS TO 440 VOLTS
SINGLE PHASE AUTOTRANSFORMER



Country/Manufacturer	Canada/RPM
----------------------	----------------------------