



OFFICIAL QUOTE

5KVA 416 VOLTS TO 200 VOLTS SINGLE PHASE AUTOTRANSFORMER



5KVA 416 VOLTS TO 200 VOLTS SINGLE PHASE AUTOTRANSFORMER


\$1,063.50 CAD

Single Phase Autotransformer with a capacity of
5kVA, transforming 416 Volts to 200 Volts

SKU: MC5G-B1

Categories: [Autotransformers](#)

SCHEMATIC/DIAGRAM AND DIMENSION PICTURES



Single Phase Autotransformer with a capacity of 5kVA, transforming 416 Volts to 200 Volts



OFFICIAL QUOTE

5KVA 416 VOLTS TO 200 VOLTS
SINGLE PHASE AUTOTRANSFORMER

PRODUCT SPECIFICATIONS

Weight	65.7 lbs
Phases	1
kVA	5
Connection	1PhA-NT-1
Primary Voltage	416
Primary Max Current	6.9A
Primary Markings	H0-H1
Primary Terminals	Terminal Blocks
Secondary Voltage	200
Secondary Max Current	14.4A
Secondary Markings	X0-X1
Secondary Terminals	Terminal Blocks
Primary Taps	N/A
Conductor Material	Copper
Insulation Class	180°C (Class F)
BIL (Insulation) Level	10kV
Efficiency (@35% Load) %	N/A
Impedance Range	1.5 – 3.5%
Sound (db)	40 dB
Enclosure Type	NEMA 1
Enclosure Size	E1-1
Finish/Colour	Polyester Powder Coat – ANSI/ASA 61 Grey
Standards & Certifications	CSA Certified File No. LR34493, UL Listed File No. E108255, ISO 9001:2015 Registered



OFFICIAL QUOTE

5KVA 416 VOLTS TO 200 VOLTS
SINGLE PHASE AUTOTRANSFORMER



Country/Manufacturer

[Canada/RPM](#)