



7.5KVA 200 VOLTS TO 347 VOLTS SINGLE PHASE AUTOTRANSFORMER

\$1,158.40 CAD

Single Phase Autotransformer with a capacity of 7.5kVA, transforming 200 Volts to 347 Volts

SKU: MC7B1-E

Categories: [Autotransformers](#)

SCHEMATIC/DIAGRAM AND DIMENSION PICTURES



Single Phase Autotransformer with a capacity of 7.5kVA, transforming 200 Volts to 347 Volts



PRODUCT SPECIFICATIONS

Weight	70.3 lbs
Phases	1
kVA	7.5
Connection	1PhA-NT-1
Primary Voltage	200
Primary Max Current	21.7A
Primary Markings	X0-X1
Primary Terminals	Terminal Blocks
Secondary Voltage	347
Secondary Max Current	12.5A
Secondary Markings	H0-H1
Secondary Terminals	Terminal Blocks
Primary Taps	N/A
Conductor Material	Copper
Insulation Class	220°C (Class H)
BIL (Insulation) Level	10kV
Efficiency (@35% Load) %	N/A
Impedance Range	1.5 – 3.5%
Sound (db)	40 dB
Enclosure Type	NEMA 1
Enclosure Size	E1-1
Finish/Colour	Polyester Powder Coat – ANSI/ASA 61 Grey
Standards & Certifications	CSA Certified File No. LR34493, UL Listed File No. E108255, ISO 9001:2015 Registered



OFFICIAL QUOTE

7.5KVA 200 VOLTS TO 347 VOLTS
SINGLE PHASE AUTOTRANSFORMER



Country/Manufacturer	Canada/RPM
----------------------	----------------------------