

OFFICIAL QUOTE

750KVA 575 VOLTS TO 415 VOLTS THREE PHASE AUTOTRANSFORMER





750KVA 575 VOLTS TO 415 VOLTS THREE PHASE AUTOTRANSFORMER


\$21,241.70 CAD

Three Phase Autotransformer with a capacity of 750kVA, transforming 575Y Volts to 415Y Volts

SKU: RC750J1-G2

Categories: Autotransformer

SCHEMATIC/DIAGRAM AND DIMENSION PICTURES





Three Phase Autotransformer with a capacity of 750kVA, transforming 575Y Volts to 415Y Volts



OFFICIAL QUOTE



750KVA 575 VOLTS TO 415 VOLTS THREE PHASE AUTOTRANSFORMER

PRODUCT SPECIFICATIONS

PRODUCT SPECIFICATIONS	
Weight	1897 lbs
Phases	<u>3</u>
kVA	<u>750</u>
Connection	3PhA-NT-1
Primary Voltage	<u>575</u>
Primary Max Current	753.1A
Primary Markings	H1-H2-H3
Primary Terminals	<u>Pads</u>
Secondary Voltage	415
Secondary Max Current	<u>1043.4A</u>
Secondary Markings	<u>X1-X2-X3</u>
Secondary Terminals	<u>Pads</u>
Primary Taps	N/A
Conductor Material	Copper
Insulation Class	220°C (Class H)
BIL (Insulation) Level	<u>10kV</u>
Efficiency (@35% Load) %	N/A
Impedance Range	1.0 - 3.0%
Sound (db)	60
Enclosure Type	NEMA 3R Indoor
Enclosure Size	<u>E3R-9</u>
Finish/Colour	Polyester Powder Coat - ANSI/ASA 61 Grey
Standards & Certifications	CSA Certified File No. LR34493, UL Listed File No. E108255, ISO 9001:2015 Registered



OFFICIAL QUOTE

750KVA 575 VOLTS TO 415 VOLTS THREE PHASE AUTOTRANSFORMER



Country/Manufacturer	<u>Canada/RPM</u>
----------------------	-------------------