



75KVA 110 VOLTS TO 380 VOLTS THREE PHASE AUTOTRANSFORMER

\$5,124.00 CAD

Three Phase Autotransformer with a capacity of 75kVA, transforming 110Y Volts to 380Y Volts

SKU: RA75A2-F

Categories: [Autotransformer](#)

SCHEMATIC/DIAGRAM AND DIMENSION PICTURES



Three Phase Autotransformer with a capacity of 75kVA, transforming 110Y Volts to 380Y Volts



PRODUCT SPECIFICATIONS

Weight	326 lbs
Phases	3
kVA	75
Connection	3PhA-NT-1
Primary Voltage	110
Primary Max Current	393.6A
Primary Markings	X1-X2-X3
Primary Terminals	Pads
Secondary Voltage	380
Secondary Max Current	114A
Secondary Markings	H1-H2-H3
Secondary Terminals	300MCM-6
Primary Taps	N/A
Conductor Material	Aluminum
Insulation Class	220°C (Class H)
BIL (Insulation) Level	10kV
Efficiency (@35% Load) %	N/A
Impedance Range	2.5 – 4.5%
Sound (db)	55
Enclosure Type	NEMA 3R Indoor
Enclosure Size	E3R-7
Finish/Colour	Polyester Powder Coat – ANSI/ASA 61 Grey
Standards & Certifications	CSA Certified File No. LR34493, UL Listed File No. E108255, ISO 9001:2015 Registered



OFFICIAL QUOTE

75KVA 110 VOLTS TO 380 VOLTS
THREE PHASE AUTOTRANSFORMER



Country/Manufacturer	Canada/RPM
----------------------	----------------------------