


OFFICIAL QUOTE

75KVA 208 VOLTS TO 400 VOLTS THREE PHASE AUTOTRANSFORMER





75KVA 208 VOLTS TO 400 VOLTS THREE PHASE AUTOTRANSFORMER


\$4,528.60 CAD

Three Phase Autotransformer with a capacity of 75kVA, transforming 208Y Volts to 400Y Volts

SKU: RA75B-G1

Categories: Autotransformer

SCHEMATIC/DIAGRAM AND DIMENSION PICTURES





Three Phase Autotransformer with a capacity of 75kVA, transforming 208Y Volts to 400Y Volts



OFFICIAL QUOTE

75KVA 208 VOLTS TO 400 VOLTS THREE PHASE AUTOTRANSFORMER



PRODUCT SPECIFICATIONS

Weight	208 lbs
Phases	<u>3</u>
kVA	<u>75</u>
Connection	3PhA-NT-1
Primary Voltage	208
Primary Max Current	208.2A
Primary Markings	<u>X1-X2-X3</u>
Primary Terminals	600MCM-2
Secondary Voltage	400
Secondary Max Current	108.3A
Secondary Markings	H1-H2-H3
Secondary Terminals	#2/0-6 AWG
Primary Taps	N/A
Conductor Material	Aluminum
Insulation Class	220°C (Class H)
BIL (Insulation) Level	<u>10kV</u>
Efficiency (@35% Load) %	N/A
Impedance Range	<u>1.5 – 3.5%</u>
Sound (db)	45
Enclosure Type	NEMA 3R Indoor
Enclosure Size	<u>E3R-6</u>
Finish/Colour	Polyester Powder Coat - ANSI/ASA 61 Grey
Standards & Certifications	CSA Certified File No. LR34493, UL Listed File No. E108255, ISO 9001:2015 Registered



OFFICIAL QUOTE

75KVA 208 VOLTS TO 400 VOLTS THREE PHASE AUTOTRANSFORMER



Country/Manufacturer	Canada/RPM
----------------------	------------