

OFFICIAL QUOTE

75KVA 208 VOLTS TO 600 VOLTS THREE PHASE AUTOTRANSFORMER





75KVA 208 VOLTS TO 600 VOLTS THREE PHASE AUTOTRANSFORMER

\$6,762.00 CAD

Three Phase Autotransformer with a capacity of 75kVA, transforming 208Y Volts to 600Y Volts

SKU: RC75B-J Categories: <u>Autotransformer</u>

SCHEMATIC/DIAGRAM AND DIMENSION PICTURES





Three Phase Autotransformer with a capacity of 75kVA, transforming 208Y Volts to 600Y Volts



OFFICIAL QUOTE

75KVA 208 VOLTS TO 600 VOLTS THREE PHASE AUTOTRANSFORMER



PRODUCT SPECIFICATIONS

Weight	394 lbs
Phases	3
kVA	<u>75</u>
Connection	<u>3PhA-NT-1</u>
Primary Voltage	208
Primary Max Current	<u>208.2A</u>
Primary Markings	<u>X1-X2-X3</u>
Primary Terminals	<u>600MCM-2</u>
Secondary Voltage	<u>600</u>
Secondary Max Current	<u>72.2A</u>
Secondary Markings	<u>H1-H2-H3</u>
Secondary Terminals	<u>#2-14 AWG</u>
Primary Taps	N/A
Conductor Material	<u>Copper</u>
Insulation Class	<u>220°C (Class H)</u>
BIL (Insulation) Level	<u>10kV</u>
Efficiency (@35% Load) %	<u>N/A</u>
Impedance Range	<u>2.5 - 4.5%</u>
Sound (db)	<u>45</u>
Enclosure Type	NEMA 3R Indoor
Enclosure Size	<u>E3R-6</u>
Finish/Colour	Polyester Powder Coat – ANSI/ASA 61 Grey
Standards & Certifications	<u>CSA Certified File No. LR34493, UL Listed File No. E108255, ISO 9001:2015</u> <u>Registered</u>



OFFICIAL QUOTE

75KVA 208 VOLTS TO 600 VOLTS THREE PHASE AUTOTRANSFORMER



Country/Manufacturer

Canada/RPM