


#### **OFFICIAL QUOTE**

### 75KVA 220 VOLTS TO 575 VOLTS THREE PHASE AUTOTRANSFORMER





### 75KVA 220 VOLTS TO 575 VOLTS THREE PHASE AUTOTRANSFORMER


\$4,706.04 USD

Three Phase Autotransformer with a capacity of 75kVA, transforming 220Y Volts to 575Y Volts

**SKU:** RC75C2-J1

**Categories:** Autotransformer

#### **SCHEMATIC/DIAGRAM AND DIMENSION PICTURES**





Three Phase Autotransformer with a capacity of 75kVA, transforming 220Y Volts to 575Y Volts



### **OFFICIAL QUOTE**



## 75KVA 220 VOLTS TO 575 VOLTS THREE PHASE AUTOTRANSFORMER

#### PRODUCT SPECIFICATIONS

PRODUCT SPECIFICATIONS	
Weight	370 lbs
Phases	<u>3</u>
kVA	<u>75</u>
Connection	3PhA-NT-1
Primary Voltage	220
Primary Max Current	<u>196.8A</u>
Primary Markings	<u>X1-X2-X3</u>
Primary Terminals	600MCM-2
Secondary Voltage	575
Secondary Max Current	75.3A
Secondary Markings	H1-H2-H3
Secondary Terminals	#2/0-6 AWG
Primary Taps	N/A
Conductor Material	Copper
Insulation Class	220°C (Class H)
BIL (Insulation) Level	<u>10kV</u>
Efficiency (@35% Load) %	N/A
Impedance Range	2.5 – 4.5%
Sound (db)	45
Enclosure Type	NEMA 3R Indoor
Enclosure Size	<u>E3R-6</u>
Finish/Colour	Polyester Powder Coat - ANSI/ASA 61 Grey
Standards & Certifications	CSA Certified File No. LR34493, UL Listed File No. E108255, ISO 9001:2015 Registered



### **OFFICIAL QUOTE**

# 75KVA 220 VOLTS TO 575 VOLTS THREE PHASE AUTOTRANSFORMER



Country/Manufacturer	Canada/RPM
----------------------	------------