



**75KVA 230 VOLTS TO 240 VOLTS
THREE PHASE AUTOTRANSFORMER**



**75KVA 230 VOLTS TO 240
VOLTS THREE PHASE
AUTOTRANSFORMER**

\$1,429.10 CAD

Three Phase Autotransformer with a capacity of 75kVA, transforming 230Y Volts to 240Y Volts

SKU: RC75C1-C

Categories: [Autotransformer](#)

SCHEMATIC/DIAGRAM AND DIMENSION PICTURES



Three Phase Autotransformer with a capacity of 75kVA, transforming 230Y Volts to 240Y Volts



PRODUCT SPECIFICATIONS

Weight	20 lbs
Phases	3
kVA	75
Connection	3PhA-NT-1
Primary Voltage	230
Primary Max Current	188.3A
Primary Markings	X1-X2-X3
Primary Terminals	600MCM-2
Secondary Voltage	240
Secondary Max Current	180.4A
Secondary Markings	H1-H2-H3
Secondary Terminals	300MCM-6
Primary Taps	N/A
Conductor Material	Copper
Insulation Class	220°C (Class H)
BIL (Insulation) Level	10kV
Efficiency (@35% Load) %	N/A
Impedance Range	0.5 – 1.5%
Sound (db)	40
Enclosure Type	NEMA 1
Enclosure Size	E1-1
Finish/Colour	Polyester Powder Coat – ANSI/ASA 61 Grey
Standards & Certifications	CSA Certified File No. LR34493, UL Listed File No. E108255, ISO 9001:2015 Registered



OFFICIAL QUOTE

75KVA 230 VOLTS TO 240 VOLTS
THREE PHASE AUTOTRANSFORMER



Country/Manufacturer	Canada/RPM
----------------------	----------------------------