




75KVA 347 VOLTS TO 416 VOLTS THREE PHASE AUTOTRANSFORMER



\$2,821.40 CAD

Three Phase Autotransformer with a capacity of 75kVA, transforming 347Y Volts to 416Y Volts

SKU: RC75E-G

Categories: [Autotransformers](#)

SCHEMATIC/DIAGRAM AND DIMENSION PICTURES



Three Phase Autotransformer with a capacity of 75kVA, transforming 347Y Volts to 416Y Volts



PRODUCT SPECIFICATIONS

Weight	98 lbs
Phases	3
kVA	75
Connection	3PhA-NT-1
Primary Voltage	347
Primary Max Current	124.8A
Primary Markings	X1-X2-X3
Primary Terminals	300MCM-6
Secondary Voltage	416
Secondary Max Current	104.1A
Secondary Markings	H1-H2-H3
Secondary Terminals	#2/0-6 AWG
Primary Taps	N/A
Conductor Material	Copper
Insulation Class	220°C (Class H)
BIL (Insulation) Level	10kV
Efficiency (@35% Load) %	N/A
Impedance Range	0.5 – 1.5%
Sound (db)	45
Enclosure Type	NEMA 3R Indoor
Enclosure Size	E3R-5
Finish/Colour	Polyester Powder Coat – ANSI/ASA 61 Grey
Standards & Certifications	CSA Certified File No. LR34493, UL Listed File No. E108255, ISO 9001:2015 Registered



OFFICIAL QUOTE
75KVA 347 VOLTS TO 416 VOLTS
THREE PHASE AUTOTRANSFORMER



Country/Manufacturer	Canada/RPM
----------------------	----------------------------