



OFFICIAL QUOTE

75KVA 460 VOLTS TO 440 VOLTS
SINGLE PHASE AUTOTRANSFORMER



75KVA 460 VOLTS TO 440
VOLTS SINGLE PHASE
AUTOTRANSFORMER

\$1,172.00 CAD

Single Phase Autotransformer with a capacity of 75kVA, transforming 460 Volts to 440 Volts

SKU: MC75H1-H2

Categories: [Autotransformers](#)

SCHEMATIC/DIAGRAM AND DIMENSION PICTURES



Single Phase Autotransformer with a capacity of 75kVA, transforming 460 Volts to 440 Volts



OFFICIAL QUOTE

75KVA 460 VOLTS TO 440 VOLTS SINGLE PHASE AUTOTRANSFORMER



PRODUCT SPECIFICATIONS

Weight	81 lbs
Phases	1
kVA	75
Connection	1PhA-NT-1
Primary Voltage	460
Primary Max Current	94.1A
Primary Markings	H0-H1
Primary Terminals	#2/0-6 AWG
Secondary Voltage	440
Secondary Max Current	98.4A
Secondary Markings	X0-X1
Secondary Terminals	#2/0-6 AWG
Primary Taps	N/A
Conductor Material	Copper
Insulation Class	220°C (Class H)
BIL (Insulation) Level	10kV
Efficiency (@35% Load) %	N/A
Impedance Range	0.5 – 1.5%
Sound (db)	40 dB
Enclosure Type	NEMA 1
Enclosure Size	E1-1
Finish/Colour	Polyester Powder Coat – ANSI/ASA 61 Grey
Standards & Certifications	CSA Certified File No. LR34493, UL Listed File No. E108255, ISO 9001:2015 Registered



OFFICIAL QUOTE

**75KVA 460 VOLTS TO 440 VOLTS
SINGLE PHASE AUTOTRANSFORMER**



Country/Manufacturer

[Canada/RPM](#)