



9KVA 110 VOLTS TO 440 VOLTS THREE PHASE AUTOTRANSFORMER

\$2,199.40 CAD

Three Phase Autotransformer with a capacity of 9kVA, transforming 110Y Volts to 440Y Volts

SKU: RC9A2-H2

Categories: [Autotransformer](#)

SCHEMATIC/DIAGRAM AND DIMENSION PICTURES



Three Phase Autotransformer with a capacity of 9kVA, transforming 110Y Volts to 440Y Volts



PRODUCT SPECIFICATIONS

Weight	49 lbs
Phases	3
kVA	9
Connection	3PhA-NT-1
Primary Voltage	110
Primary Max Current	47.2A
Primary Markings	X1-X2-X3
Primary Terminals	#2-14 AWG
Secondary Voltage	440
Secondary Max Current	11.8A
Secondary Markings	H1-H2-H3
Secondary Terminals	Terminal Blocks
Primary Taps	N/A
Conductor Material	Copper
Insulation Class	220°C (Class H)
BIL (Insulation) Level	10kV
Efficiency (@35% Load) %	N/A
Impedance Range	2.5 – 4.5%
Sound (db)	40
Enclosure Type	NEMA 1
Enclosure Size	E1-3
Finish/Colour	Polyester Powder Coat – ANSI/ASA 61 Grey
Standards & Certifications	CSA Certified File No. LR34493, UL Listed File No. E108255, ISO 9001:2015 Registered



OFFICIAL QUOTE
9KVA 110 VOLTS TO 440 VOLTS
THREE PHASE AUTOTRANSFORMER



Country/Manufacturer	Canada/RPM
----------------------	----------------------------