



9KVA 230 VOLTS TO 416 VOLTS THREE PHASE AUTOTRANSFORMER

\$1,620.10 CAD

Three Phase Autotransformer with a capacity of
9kVA, transforming 230Y Volts to 416Y Volts

SKU: RC9C1-G

Categories: [Autotransformer](#)

SCHEMATIC/DIAGRAM AND DIMENSION PICTURES



Three Phase Autotransformer with a capacity of 9kVA, transforming 230Y Volts to 416Y Volts



PRODUCT SPECIFICATIONS

Weight	27 lbs
Phases	3
kVA	9
Connection	3PhA-NT-1
Primary Voltage	230
Primary Max Current	22.6A
Primary Markings	X1-X2-X3
Primary Terminals	Terminal Blocks
Secondary Voltage	416
Secondary Max Current	12.5A
Secondary Markings	H1-H2-H3
Secondary Terminals	Terminal Blocks
Primary Taps	N/A
Conductor Material	Copper
Insulation Class	220°C (Class H)
BIL (Insulation) Level	10kV
Efficiency (@35% Load) %	N/A
Impedance Range	1.5 – 3.5%
Sound (db)	40
Enclosure Type	NEMA 1
Enclosure Size	E1-3
Finish/Colour	Polyester Powder Coat – ANSI/ASA 61 Grey
Standards & Certifications	CSA Certified File No. LR34493, UL Listed File No. E108255, ISO 9001:2015 Registered



OFFICIAL QUOTE

9KVA 230 VOLTS TO 416 VOLTS

THREE PHASE AUTOTRANSFORMER



Country/Manufacturer	Canada/RPM
----------------------	----------------------------