

**OFFICIAL QUOTE** 

## 9KVA 415 VOLTS TO 380 VOLTS THREE PHASE AUTOTRANSFORMER






# 9KVA 415 VOLTS TO 380 VOLTS THREE PHASE AUTOTRANSFORMER

# \$970.80 CAD

Three Phase Autotransformer with a capacity of 9kVA, transforming 415Y Volts to 380Y Volts

SKU: RC9G2-F Categories: <u>Autotransformer</u>

### SCHEMATIC/DIAGRAM AND DIMENSION PICTURES





Three Phase Autotransformer with a capacity of 9kVA, transforming 415Y Volts to 380Y Volts



**OFFICIAL QUOTE** 

## 9KVA 415 VOLTS TO 380 VOLTS THREE PHASE AUTOTRANSFORMER



#### **PRODUCT SPECIFICATIONS**

| Weight                     | 20 lbs  |
|----------------------------|---|
| Phases                     | <u>3</u>  |
| kVA                        | <u>9</u>  |
| Connection                 | <u>3PhA-NT-1</u>  |
| Primary Voltage            | <u>415</u>  |
| Primary Max Current        | <u>12.5A</u>  |
| Primary Markings           | <u>H1-H2-H3</u>   |
| Primary Terminals          | Terminal Blocks   |
| Secondary Voltage          | <u>380</u>  |
| Secondary Max Current      | <u>13.7A</u>  |
| Secondary Markings         | <u>X1-X2-X3</u>   |
| Secondary Terminals        | Terminal Blocks   |
| Primary Taps               | N/A   |
| Conductor Material         | <u>Copper</u>   |
| Insulation Class           | <u>180°C (Class F)</u>  |
| BIL (Insulation) Level     | <u>10kV</u>   |
| Efficiency (@35% Load) %   | <u>N/A</u>  |
| Impedance Range            | <u>0.5 – 1.5%</u>   |
| Sound (db)                 | <u>40</u>   |
| Enclosure Type             | NEMA 1  |
| Enclosure Size             | <u>E1-1</u>   |
| Finish/Colour              | Polyester Powder Coat – ANSI/ASA 61 Grey  |
| Standards & Certifications | <u>CSA Certified File No. LR34493, UL Listed File No. E108255, ISO 9001:2015</u><br><u>Registered</u> |



**OFFICIAL QUOTE** 

#### 9KVA 415 VOLTS TO 380 VOLTS THREE PHASE AUTOTRANSFORMER



Country/Manufacturer

Canada/RPM