




OFFICIAL QUOTE

9KVA 416 VOLTS TO 575 VOLTS THREE PHASE AUTOTRANSFORMER



9KVA 416 VOLTS TO 575 VOLTS THREE PHASE AUTOTRANSFORMER


\$1,513.80 CAD

Three Phase Autotransformer with a capacity of 9kVA, transforming 416Y Volts to 575Y Volts

SKU: RC9G-J1

Categories: [Autotransformers](#)

SCHEMATIC/DIAGRAM AND DIMENSION PICTURES



Three Phase Autotransformer with a capacity of 9kVA, transforming 416Y Volts to 575Y Volts



OFFICIAL QUOTE

9KVA 416 VOLTS TO 575 VOLTS
THREE PHASE AUTOTRANSFORMER

PRODUCT SPECIFICATIONS

Weight	20 lbs
Phases	3
kVA	9
Connection	3PhA-NT-1
Primary Voltage	416
Primary Max Current	12.5A
Primary Markings	X1-X2-X3
Primary Terminals	Terminal Blocks
Secondary Voltage	575
Secondary Max Current	9A
Secondary Markings	H1-H2-H3
Secondary Terminals	Terminal Blocks
Primary Taps	N/A
Conductor Material	Copper
Insulation Class	180°C (Class F)
BIL (Insulation) Level	10kV
Efficiency (@35% Load) %	N/A
Impedance Range	1.0 – 3.0%
Sound (db)	40
Enclosure Type	NEMA 1
Enclosure Size	E1-1
Finish/Colour	Polyester Powder Coat – ANSI/ASA 61 Grey
Standards & Certifications	CSA Certified File No. LR34493, UL Listed File No. E108255, ISO 9001:2015 Registered



OFFICIAL QUOTE

9KVA 416 VOLTS TO 575 VOLTS
THREE PHASE AUTOTRANSFORMER



Country/Manufacturer

[Canada/RPM](#)