



BA112H-N1/EP \$13,950.21 USD

SKU: f3e55ebfbcac Categories: <u>Encapsulated Isolation Transformer</u>

SCHEMATIC/DIAGRAM AND DIMENSION PICTURES





PRODUCT SPECIFICATIONS

| Weight | 1365 lbs |
|---------------------|---------------------|
| Phases | <u>3</u> |
| kVA | <u>112.5</u> |
| Connection | <u>3Ph-DY-5T-SD</u> |
| Primary Voltage | <u>480</u> |
| Primary Max Current | <u>135.3A</u> |
| Primary Markings | <u>H1-H2-3</u> |
| Primary Terminals | <u>300MCM-6</u> |



BA112H-N1/EP



| Secondary Voltage | 400Y/231 |
|----------------------------|---|
| Secondary Max Current | <u>41.6A</u> |
| Secondary Markings | <u>X0-X1-X2-X3</u> |
| Secondary Terminals | <u>300MCM-6</u> |
| Primary Taps | <u>+/-2 x 2.5%</u> |
| Conductor Material | Aluminum |
| Temperatue Rise | <u>130°C</u> |
| Insuation Class | <u>200°C</u> |
| BIL (Insulation) Level | <u>10kV</u> |
| Efficiency | N/A |
| Impedance | <u>1.5 – 3.5%</u> |
| Sound (db) | <u>50</u> |
| Enclosure Type | NEMA 3R Indoor |
| Enclosure | E3R-3PEP-8 |
| Finish | Polyster Powder Coat – ANSI/ASA 61 Grey |
| Standards & Certifications | CSA Certified File No. LR34493, UL Listed File No. E108255, ISO 9001:2015 Registered |