



BA30J-F/EP

\$3,085.00 CAD

SKU: 08eae55d4ee3

Categories: [Encapsulated Isolation Transformer](#)

SCHEMATIC/DIAGRAM AND DIMENSION PICTURES



PRODUCT SPECIFICATIONS

| | |
|----------------------------|------------------------------|
| Weight | 520 lbs |
| Phases | 3 |
| kVA | 30 |
| Connection | 3Ph-DY-5T-SD |
| Primary Voltage | 600 |
| Primary Max Current | 28.9A |
| Primary Markings | H1-H2-3 |
| Primary Terminals | #2-14 AWG |



| | |
|---------------------------------------|------------------------------------------------------------------------------------------------------|
| Secondary Voltage | 380Y/220 |
| Secondary Max Current | 45.6A |
| Secondary Markings | X0-X1-X2-X3 |
| Secondary Terminals | #2-14 AWG |
| Primary Taps | +/- 2 x 2.5% |
| Conductor Material | Aluminum |
| Temperatue Rise | 130°C |
| Insuation Class | 200°C |
| BIL (Insulation) Level | 10kV |
| Efficiency | N/A |
| Impedance | 1.5 – 3.5% |
| Sound (db) | 45 |
| Enclosure Type | NEMA 3R Indoor |
| Enclosure | E3R-3PEP-5 |
| Finish | Polyster Powder Coat – ANSI/ASA 61 Grey |
| Standards & Certifications | CSA Certified File No. LR34493, UL Listed File No. E108255, ISO 9001:2015 Registered |